



AMX Device Discovery



Closed Captioning



Crestron Integrated Partner

Key Features

- 2,200 ANSI Lumens
- Native XGA Resolution
- 500:1 Contrast Ratio
- 8.2 lbs.
- Easily accessible hybrid filter (5,000 hours between maintenance)
- Lamp life approximately 6,000 Hours (Eco Mode)*
- Audio Pass Through
- 16W Speaker Output
- 0.5 watt power saving mode using 120V
- Template Function
- 2 RGB In, 1 RGB out / Composite / S-Video
- Instant On/Off
- Security Bar / Transition Detector
- 29 dB (Eco Mode)



Specifications



Model Name	CP-X2011 Series
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	Video 540 TV lines RGB 1024 dots X 768 lines
Colors	16.7 million colors
Aspect Ratio	Native 4:3/16:9 compatible
Lens	manual zoom x 1.2
Throw Ratio (distance : width)	1.5 - 1.8 : 1
Lamp	190W UHB
Brightness	2,200 ANSI Lumens
Expected lamp Life	Approximately 3,000 hours (normal) 6,000 hours (Eco mode)*
Contrast Ratio	500 : 1
Speaker Output	16W (2 x 8W speakers)
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption	330W
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	RGB Composite Video Component Video
Acoustic Noise Level	35 dB (29 dB in Eco Mode)
H-Sync	15 Hz - 106 Hz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 30°
Approvals	UL, C-UL, FCC, CE, RoHS
RGB Input	Analog RGB
RGB Output	RGB
Video Input	S-Video Composite Video Component Video
Audio	Input Output
Ethernet	
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)
Other	USB connector (USB mouse) x 1
Dimensions (W x D x H)	12.5" x 3.9" x 11.3"
Weight	8.2 lbs.
Closed Caption	CC1, CC2, CC3, CC4, T1, T2, T3, T4
Additional Features	Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard More, Input Source Naming, MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side

Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual CPX2010LAMP (DT01021)
Lamp	HL02483
Remote Control	MU06481
Filter	

Screen Size 4:3 Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	83
80	64	94	112
100	80	118	140
120	96	142	168
150	120	177	211
200	160	237	281
300	240	356	422

Throw Ratio: 1.5 - 1.8:1 (distance : width)
*Measured in inches

